



# AUTOMATIC, COMPLETE SALT TREATMENT

# TRi Expert

# 1 AUTOMATIC REGULATION OF PH AND OF DISINFECTION

The TRi Expert chlorinator constantly monitors and maintains water quality thanks to its 2 optional or built-in modules:

- pH Link, automatic pH regulator
- **Dual Link**, automatic pH and chlorine production regulator

# **2** REMOTE CONTROL

TRi Expert is 100% compatible with the Zodiac<sup>®</sup> **AquaLink**<sup>®</sup> automation system. So, the pool can be remotely operated 24/7 via the iAquaLink<sup>™</sup> smartphone app.

## **3** PERFECT FOR ALL POOLS, AND ESSENTIAL FOR LARGE POOLS

In the Zodiac<sup>®</sup> range, TRi Expert is the salt electrolysis solution that can be used to **treat large pools** of up to 170 m<sup>3</sup>.







#### SPECIFICATIONS

#### FOR WHICH TYPE OF POOLS?



#### Safe system

Automatic stop if there is no flow in the cell.



### Minimal maintenance

Self-cleaning electrodes using reverse polarity.



GARANTIE

CONDITION

# Reliability

Titanium electrodes coated with an exclusive alloy.

Unconditional warranty

On the control box and the cell, whatever the causes of damage.





#### 2 POOLS UP TO 170M<sup>3</sup> (TEMPERATE CLIMATE, FILTRATION 8 HR/DAY)



#### **STANDARD FEATURES**





Glued reducer kit

Flow detector kit





Wall mounting kit

Pump connection kit

TECHNICAL INFORMATION				
MODELS	TRi Expert 10	TRi Expert 18	TRi Expert 22	TRi Expert 35
Volume of water treated (temperate climate, filtration 8 hours/day)	40 m <sup>3</sup>	70 m³	100 m³	170 m³
Nominal chlorine production	10 g/hr	18 g/hr	22 g/hr	35 g/hr
User interface	4-line backlit LCD screen			
Operating mode(s)	Normal, Boost, Low (shutter mode)			
Reverse polarity	Yes: 2.5 or 5 hour (factory setting = 5 hour)			
Recommended salt level - minimum	4 g/L - 3.3 g/L minimum			
Safety	"Low salt" indicator: reduced production to protect the electrode			
	"No flow" indicator: production is stopped until optimal conditions return			
	Mechanical flow sensor			
Working life of the cell	10,000 hours (titanium plates, SC6 ruthenium treatment)			
Power rating	195 W			

#### ADDITIONAL EQUIPMENT



pH Link module



Dual Link module



AquaLink® TRi

pH sensor testers - Redox



RCS Paris 395 068 679 - @Photo Credits: ZODIAC<sup>®</sup> - ZODIAC<sup>®</sup> is a registered trademark of Zodiac International, S.A.S.U., used under license - www.le-fil.fr - WL15578

Salt chlorinators are an **automatic and efficient** disinfection solution.

They are easy to use, offer complete water treatment and reduce maintenance.



## www.zodiac-poolcare.com